

Model JSOF-250H 350 °C Hi-Temp. Oven



High-Temperature Forced Convection Oven provides higher temperature up to +350°C than conventional ovens for special application for material research or testing laboratory. Motorized fan to force air circulation across heating elements and circulates into the chamber.

The fan allows more consistent distribution of air and optional inert gas (Nitrogen Gas) purge system prevents oxidation of samples at a high temperature treatment.

MAIN FEATURES

PERFORMANCE

- Control Temperature Range from ambient +10 °C to 350 °C
- Forced air convection for fast drying application
- Aero-dynamic chamber designed with circulation blower to achieve superior thermal uniformity
- Separate heating compartment located on side wall for contamination free and maintenance free
- 50mm thick high thermal efficiency mineral wool with woven aluminum barrier sheet saves energy and less dust

CONTROLLER

- ±0.1 °C Digital PID Controller with LED Display
- Automatic START/STOP timer
- Adjustable timer scale 99min 59sec / 99hr 59min / 99 day 23hr or continuous operation
- Temperature calibration
- Auto-tuning function
- CA(K)-Type sensor

CONSTRUCTION

- Durable epoxy powder coated metallic casing
- Corrosion resistant Stainless Steel 304 chamber
- Ventilation damper

CONVENIENCE

- Corrosion resistant Stainless Steel 304 Chamber
- Removable and height adjustable shelf by 25mm spacing
- Outer door with ceramic gasket and compression door lock
- Opening size adjustable ventilation damper
- Non-contact door switch cut-off heater and blower
- High temperature resistant ceramic fiber door gasket
- Opening size adjustable ventilation damper
- Door switch cut-off heater and blower to protect user from exposure to hot air

SAFETY

- DUAL OVER TEMP. CUT-OFF
 - Digital system cut-off heater and AUDIO VISUAL ALARM in case +2 °C above set temperature
 - Analog system cut-off heater 10% above set temp.
- MAX TEMP CUT-OFF heater and AUDIO VISUAL ALARM when +1 °C above maximum limit
- DOOR SENSOR cut-off heater and blower when door opened
- SENSOR DISCONNECTION ALARM
- OVER CURRENT CUT-OFF : Electrical Leakage Breaker

SPECIFICATIONS**Art. No. JSOF-250H****Dimension Data**

Chamber Volume	250 Liters
Inner Dims. (W x D x H mm)	600 x 600 x 700
Outer Dims. (W x D x H mm)	1045 x 760 x 980
No. of Shelf Positions	20 ea
3No. of Shelf included	3 ea
No. of Ventilation Damper	1 ea

Performance Data

Heating System	Forced Air Convection
Temp. Range	Amb. +10 °C ~ +350 °C
Accuracy at 120 °C	±1.0 °C
Uniformity at 120 °C	±2.0 °C
Heat up time to 200 °C	15 min.

Controller

Processor	Digital Microprocessor PID Temperature Controller
Display	Digital LED Display
Calibration	1 Point Temperature OFFSET Calibration
Resolution	0.1 °C
Auto-Stop Timer	1 min. ~ 99 hr 59 min
Auto-Start Time	1 min. ~ 99 hr 59 min
Sensor	CA(K)-Type
Power Restoration	Power and Timer Restoration Function in case of power outage
PC Communication Interface	RS-232C PC COMMUNICATION INTERFACE [OPTION]

Safety Data

Safety Device	DUAL OVER TEMP. CUT-OFF Digital system cut-off heater and AUDIO VISUAL ALARM Analog system cut-off heater 10% above set temp. MAX TEMP CUT-OFF heater and AUDIO VISUAL ALARM CUT-OFF heater and blower when door opened SENSOR DISCONNECTION ALARM Over Current CUT-OFF
---------------	---

Material Data

Body	Epoxy Powder Coated Steel
Chamber	Stainless Steel 304 (AISI304)
Insulation	50 mm Woven Mineral Wool

Electrical Data

Rated voltage	220 ± 10% VAC
Power frequency	50 / 60Hz
Heater Output	4.0 kW
Nominal power	4.1 kW 18.6 amp
Phase	1 Phase
Plug configuration	30 AMP Plug

Usable Condition

Temp. & Humidity	5°C - 40°C, < 80% RH
------------------	----------------------

Packaging Data

Type of packaging	Carton on a wooden palette
Shipping Dims. (W x D x H mm)	1200 x 900 x 1120
Net Weight	116.0 kg
Shipping Weight	189.0 kg

ORDERING INFORMATION

Art. No.	Descriptions	Voltage
JSOF-250H	Hi Temp. Forced Convection Oven, 250 L	220 VAC 1~ ph 50/60Hz

OPTIONAL ACCESSORIES

Art No.		
PHS-A25	Perforated Shelf, Stainless Steel 304 for JSOF-250H	W570 x D570 mm
PHS-B25	Wire Shelf, Stainless Steel 304 for JSOF-250H	W570 x D570 mm
PHS-A99	Shelf Support, Set of 4	
PHC-001	Nitrogen Gas Purge System, Gas inlet/outlet fitting with valve, flow meter	

JS RESEARCH INC.

Gongju-City, Korea
 TEL +82 41 856 3677
 FAX +82 41 856 3679
 info@jsresearch.co.kr
 www.jsr.kr