

COMMODITY DESCRIPTION

H.S. No	Item No	Description	Unit	Quantity
		Floor Standing Shaking Incubator	set	1

A. Model : JSSI-300T

B. Product Description : Shaking Incubator

C. Manufacturer / Origin : JS Research Inc. / Korea

D. Application :

JSSI-300T Floor Standing Shaking Incubator is ideal for any shaking application requiring controlled temperature and speed for microbiology, cell biology, cell culture, tissue culture, biochemistry, molecular biology, environmental engineering, soil testing field temperature range from ambient + 5 °C to +70 °C and shaking speed from 20 ~ 350 rpm.

E. Photo



JSSI-300T Floor Standing Shaking Incubator

F. Feature

JSC-7S Integrated Digital PID Controller

- ✓ Temperature control with ± 0.1 °C
- ✓ Shaking speed control within ± 1 rpm
- ✓ Temperature and shaking can be controlled together or independently with timer
- ✓ Automatic STOP timer Max. 99min 59sec / 99hr 59min / 99day 23hr
- ✓ Dual digital LED displays TEMP, RPM and remaining TIME
- ✓ Temperature calibration
- ✓ Shaking speed calibration
- ✓ Slow Start and Stop Control
- ✓ Auto-tuning function
- ✓ Class A Pt-100 Ω sensor
- ✓ Power back-up function when power failure.

Construction

- ✓ Durable epoxy powder coated metallic casing
- ✓ Corrosion resistant Stainless Steel 304 chamber
- ✓ Self-balanced door with magnetic packing, double layer glass window
- ✓ 4 ea x caster and level foot for self balancing and anti-vibration

Performance

- ✓ Forced circulation for excellent thermal uniformity within ± 0.2 °C
- ✓ Separate heating compartment prevents contamination and maintenance free
- ✓ Durable shaking mechanism with powerful AC motor supports orbital or reciprocal shaking motion

Convenience

- ✓ Easy-to-open self-balanced door with air tight self adhesive magnetic packing and double layer glass window, lighting in chamber for easy observation during cultivation
- ✓ Door switch to cut-off shaking motion when put in and out sample
- ✓ Caster and height adjustable level feet for easy transport, balancing and anti-vibration
- ✓ Various choice of shaking platforms
- ✓ Adjustable automatic defrost system

Safety

- ✓ DUAL OVER TEMP. CUT-OFF
Digital system cut-off heater and AUDIO VISUAL ALARM in case +2 °C above set temperature
Analog system cut-off heater 10% above set temp.
- ✓ MAX TEMP CUT-OFF heater and AUDIO VISUAL ALARM when +1 °C above maximum limit
- ✓ OVER SPEED CUT-OFF
Digital system automatically cut-off motor in case +10 rpm above set rpm.
- ✓ SENSOR DISCONNECTION ALARM
- ✓ Motor failure ALARM
- ✓ Shaking motion automatically stops when door opened
- ✓ OVER CURRENT CUT-OFF : Electric Leakage Breaker

G. Specifications

Chamber Volume (Capacity)	204 Liters
Inner Dims. (W x D x H)	760 x 715 x 375 mm
Outer Dims. (W x D x H)	1080 x 875 x 975 mm
Platform Dims. (W x D)	700 x 650 mm
Heating	Forced Air Convection
Cooling	none
Temp. Range	amb. +5 °C ~ +70 °C
Accuracy	±0.2 °C at +37 °C
Uniformity	±1.0 °C at +37 °C
Shaking Mode	Orbital Reciprocal with optional adaptor
Shaking speed range	20 ~ 350 rpm
Shaking Stroke	20 mm
Shaking speed accuracy	±1 rpm
Control	Integrated Digital PID microprocessor control system Digital display of PV and SV for temperature, rpm and time Timer : 99min 59sec / 99hr 59min / continuous time scale selectable
Sensor	Class A PT-100 Ω Sensor

Safety	Over-Temperature Cut-Off Over-Speed Cut-Off Over Current Cut-Off
Material	Body : Epoxy Powder Coated Steel, 1.0 mm thickness Chamber : Stainless Steel 304, 0.8 mm thickness Glass Window : Double Layer Tempered Safety, 5 mm thickness
Electrical Requirement	220 \pm 10% VAC, 50/60Hz, 1-Phase
Heater Capacity	700 W
Power Rating	3.2 amps
Plug Configuration	CEE 7/7 Schuko or BS 1363
Net Weight	130 kg
Shipping Weight	180 kg
Shipping Dims. (W x D x H)	1230 x 1010 x 1130 mm, wooden crating

H. Standard Accessories

Instruction Manual : 1 EA
Warranty Card : 1 EA

I. Options & Accessories

Art No.	Descriptions
PHF-P11	Adaptor Kit for Reciprocal Motion
PHF-U70	Universal Spring Rack W690 x D650 mm Flask loading capacity (approx. 42 x 100ml, 25 x 250ml, 19 x 500ml, 15 x 1000ml, 8 x 2000ml)
PHF-P70	Universal Flask Holder Platform W700 x D650 mm Flask loading capacity (approx. 41 x 100ml, 25 x 250ml, 25 x 500ml, 16 x 1000ml, 9 x 2000ml, 9 x 3000ml, 5 x 5000ml)
PHF-P71	Dedicated Flask Holder Platform W700 x D650 mm including 72 ea x 50 ~ 100 ml polycarbonate flasks holder
PHF-P72	Dedicated Flask Holder Platform W700 x D650 mm including 42 ea x 200 ~ 300 ml polycarbonate flasks holder

PHF-P73	Dedicated Flask Holder Platform	W700 x D650 mm
	including 25 ea x 500 ~ 1000 ml polycarbonate flasks holder	
PHF-M70	Non-Slip Rubber Mat	W700 x D650 mm
PHF-P01	Polycarbonate Flask Holder 50 ~ 100 ml Size Adjustable	
PHF-P02	Polycarbonate Flask Holder 200 ~ 300 ml Size Adjustable	
PHF-P03	Polycarbonate Flask Holder 500 ~ 1000 ml Size Adjustable	
PHF-S01	Stainless Steel Flask Holder 100 ml	
PHF-S02	Stainless Steel Flask Holder 250 ml	
PHF-S03	Stainless Steel Flask Holder 500 ml	
PHF-S04	Stainless Steel Flask Holder 1000 ml	
PHF-S05	Stainless Steel Flask Holder 2000 ml	
PHF-S06	Stainless Steel Flask Holder 3000 ml	
PHF-S07	Stainless Steel Flask Holder 5000 ml	
PHF-T01	Test Tube Holder 8 mm Dia. for 80 test tubes	
PHF-T01	Test Tube Holder 10 mm Dia. for 80 test tubes	
PHF-T01	Test Tube Holder 12 mm Dia. for 54 test tubes	
PHF-T01	Test Tube Holder 14 mm Dia. for 54 test tubes	
PHF-T01	Test Tube Holder 16 mm Dia. for 30 test tubes	
PHF-T01	Test Tube Holder 25 mm Dia. for 15 test tubes	
PHF-T01	Test Tube Holder 35 mm Dia. for 8 test tubes	

J. Warranty

1 Year full coverage warranty