

Model JSSK-3D : 3D Rocker



Model JSSK-3D 3D Rocker

MAIN FEATURES

Controller

- Advanced MCU processor applies precise speed control technology
- 6 Preset Programs
- 10 Steps for each program
- Touch-sensitive Multi-Functional Capacitive Button compatible to all kind of latex gloves as well as finger touch.
- Easy-to-use Jog Dial for quick and convenient setting of speed and timer. Push to Run and Stop control.
- High-fidelity clear back light LCD displays complete setting and operating condition at a glance. Easy to monitoring set values, present speed and time.

Construction

- Silent BLDC motor
- Rugged and low profile ABS plastic body
- Light weighted aluminum shaking platform

Performance

- Speed range 10 to 70 rpm
- 9° Tilt Angle
- Digital Timer set up to 99hr 59min by 1 min
- W350 x D350 mm standard shaking platform
- Powerful driving mechanism with “Slow Start Function”
- Silent BLDC motor provides long shelf life and maintenance free
- Maximum loading capacity up to 10 kgs

Convenience

- Interchangeable shaking platform
- Anti-Slip Silicone Mat

Safety

- Over load protection
- Over current protection

SPECIFICATIONS

Description	MODEL JSSK-3D
Performance Data	
Type of Shaking	3D Orbital
Platform Dimensions (W x D mm)	350 x 350
Speed Range	10 to 70 rpm, 1 rpm resolution
Shaking Angle	9° Tilt Angle
Max Load	10 kgs

Controller	
Type	Digital Fuzzy Control with Capacitive Touch Button and Jog Dial
Timer	99hr 59min by 1 min resolution
Display	Full Size Digital Back Light LCD Display Independent ON/OFF Switch
Program Function	6 Preset Programs, 10 Steps for each program

Platform Dimensions	
Universal Spring Rack	W350 x D350 mm
Universal Silicone Mat Platform	W350 x D350 mm

Motor	
Type	Brushless DC Motor
Power	45 Watt
Rotating Direction	Clockwise

Safety Data	
Safety Device	Over Load Protection Over Current Protection

Material Data	
Body	ABS
Platform	Aluminum

Electrical Data

Technical Data Model JSSK-3D

Rated voltage	230 ± 10% VAC
Power frequency	50/60 Hz
Nominal power	45 Watt
Phase	1 Phase
Plug configuration	CEE 7/7 Schuko or BS 1363

Usable Condition

Temp. & Humidity	5°C - 40°C, < 80% RH
------------------	----------------------

Packaging Data

Shipping Dims. (W x D x H)	600 x 590 x 320 mm
Type of packaging	Carton
Net Weight	11.5 kg
Shipping Weight	14.5 kg

ORDERING INFORMATION

Art. No.	Descriptions	Voltage
JSSK-3D	3D Rocker	230 VAC 1 ph 50/60 Hz

ACCESSORIES



PHF-P35SET
 PHF-P35 Universal Flask Holder
 Platform
 PHF-M35 Silicone Mat
 PHF-S35 Elastic String Band



PHF-U35 Universal Spring Rack

ACCESSORIES

Art. No.	Descriptions
PHF-P35SET	PHF-P35 Universal Flask Holder Platform W370 x D370 mm PHF-M35 Silicone Mat W350 x D350 mm PHF-S35 Elastic String Band x 2 Set
PHF-U35	Universal Spring Rack W350 x D350 mm
PHF-M35	Silicone Mat W350 x D350 mm
PHF-S35	Elastic String Band with Stopper x 2 Set

JS RESEARCH INC.

Gongju-City, Korea

TEL +82 41 856 3677

FAX +82 41 856 3679

info@jsresearch.co.kr

www.jsr.kr